

SET3.1: PIT es3.1 / 2 n/c

400510

PITestop, E-STOP/contact block set, consisting of E-STOP pushbutton with contact block, 2 N/C terminals (screw type).



Technical details

General data	
Approval:	TÜV, EAC (Eurasian)
Self-monitored:	yes
Technical data	
Electrical data	
Min. contact current:	1 mA
Emergency stop	
Switch cap. E-STOP to standard:	EN 60947-5-1
Contact material E-STOP:	AgNi
Environmental data	
Ambient temperature:	-30 - 70 °C
Pollution degree clear.&creep.:	3
Protection type, housing:	IP65
Mechanical data	
Connection terminal:	Screw terminal
Height dimension:	41.5 mm
Width dimension:	27 mm
Depth dimension:	43.6 mm
Diameter:	55 mm
Net weight:	77 g

Gross weight:	80 g
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	no
REACH compliance:	Contains no SVHC substances
WEEE classification (08/2018):	5 devices (feed size < 50cm)
Commercial data	
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27371244
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000017
ETIM Reference Feature:	EC002034
UNSPSC 25:	46171620
GTIN:	4046548043686
Volume:	0 dm3
Harmonized System Code:	85365080
Type of tariff number:	TARIC
Use of customs tariff number:	Ausfuhr, Einfuhr
Quantity per packaging unit:	1