

PIT m3 key2 mode 2

402282



PITmode transponder key for electronic operating mode selector switch PIT m3.xp, material: Plastic actuator, permission for OM1/2.

Technical details

General data

Approval:	CE, UKCA, TÜV
Sensor principle:	Transponder
Transponder coding:	0x1111 (PILZ)

Technical data

Environmental data

Ambient temperature:	-20 - 60 °C
----------------------	-------------

Mechanical data

Height dimension:	8.6 mm
Width dimension:	35 mm
Depth dimension:	60.2 mm
Net weight:	9 g
Gross weight:	10 g

Transponder

Transponder energy supply:	Passive (battery-free)
Operating frequency:	125 kHz

Environment

RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	no

REACH compliance:	Contains no SVHC substances
WEEE classification (08/2018):	5 devices (feed size < 50cm)
Commercial data	
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27371292
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000017
ETIM Reference Feature:	EC002024
UNSPSC 25:	32131023
GTIN:	4046548084368
Volume:	0 dm3
Harmonized System Code:	85389099
Type of tariff number:	TARIC
Use of customs tariff number:	Ausfuhr, Einfuhr
Quantity per packaging unit:	1