

## PSEN me5S NC-NC.NC-NC 1switch

6L000018



Mechanical safety gate system PSENmech, interlock principle springforce, contacts interlocking 2 N/C, contacts guard locking 2 N/C, supplyvoltage 24 V AC/DC.

## Technical details

### General data

|                                 |                          |
|---------------------------------|--------------------------|
| Approval:                       | CSA, CE, CCC, UKCA, DGUV |
| Suitable for series connection: | yes                      |
| unit type:                      | Sensor                   |

### Technical data

#### Electrical data

|                            |           |
|----------------------------|-----------|
| Supply voltage (V):        | 24 - 24 V |
| Type of supply voltage U1: | AC/DC     |

#### Relay outputs

|                                 |              |
|---------------------------------|--------------|
| Utilisation cat. AC15/DC13sta.: | EN 60947-5-1 |
| Voltage AC15 safety cont.:      | 240 V        |
| Max. current AC15 safety cont.: | 1.5 A        |
| Voltage DC13 safety cont.:      | 250 V        |

### Environmental data

|                           |             |
|---------------------------|-------------|
| Ambient temperature:      | -25 - 55 °C |
| Overvoltage category:     | II          |
| Protection type, housing: | IP67        |

### Mechanical data

|                   |        |
|-------------------|--------|
| Holding force:    | 1500 N |
| Height dimension: | 192 mm |

|                                |                              |
|--------------------------------|------------------------------|
| Width dimension:               | 42 mm                        |
| Depth dimension:               | 44 mm                        |
| Net weight:                    | 489 g                        |
| Gross weight:                  | 541 g                        |
| Environment                    |                              |
| RoHS directive:                | 2011/65/EU, 2015/863/EU      |
| RoHS conformity:               | yes                          |
| RoHS exceptions:               | no                           |
| REACH compliance:              | Contains no SVHC substances  |
| WEEE classification (08/2018): | 5 devices (feed size < 50cm) |
| Commercial data                |                              |
| ECLASS version:                | ECLASS-13                    |
| ECLASS Reference Feature:      | 27272603                     |
| ETIM Version:                  | ETIM-9.0                     |
| ETIM Reference Group:          | EG000026                     |
| ETIM Reference Feature:        | EC002593                     |
| UNSPSC 25:                     | 39122205                     |
| GTIN:                          | 4046548101478                |
| Volume:                        | 1.258 dm3                    |
| Harmonized System Code:        | 85365080                     |
| Type of tariff number:         | TARIC                        |
| Use of customs tariff number:  | Ausfuhr, Einfuhr             |
| Quantity per packaging unit:   | 1                            |

## Optional accessories



570793

PSEN cable 200m-8x0.25mm<sup>2</sup>



6L000005

PSEN me5 escape release



6L000006

PSEN me5 20mm extension



6L000007

PSEN me5 40mm extension



6L000008

PSEN me5 emergency release front



6L000009

PSEN me5 emergency release back