

GF3 Glass fiber Ø 3 mm - without metercounter

Cable pulling system for pipe diameter 10-50 mm

Item no.: 10196 | 10197 | 10198



VIDEO

GF3

[Click here Video](#)

KG 130

PATENTED

[Click here Productinformation](#)

Content accessory box (16-parts)

Easy service opening / accessory box

Anti-slip coating

Just open one screw

Accessory box 16-parts

Rod	Rec. pipe ID	Bending radius w.e. joint	Bending radius rod	Breaking load	Total breaking load
Ø					
3 mm	9 – 45 mm	38 mm	28 mm	450 kg	130 kg

DATA

ITEM NO.	10196	10197	10198
LENGTH	20 m	30 m	50 m
TOTAL WEIGHT	1,26 kg	1,40 kg	1,56 kg
MATERIAL ROD	Fiberglass core with PP sheath		
BENDING RADIUS	38 mm		
PIPE INNER Ø	optimal from 9 mm - 45 mm		
DIMENSION	L: 295 mm x B: 245 mm x H: 74 mm		
EAN-CODE - 10192	9120045476729		
EAN-CODE - 10193	9120045477122		
EAN-CODE - 10195	9120045477139		

BESCHREIBUNG

GF3 - Cable pulling tool without meter counter, glass fibre rod Ø 3 mm with kink protection ending joint and patented guiding head with swivel. Stowed in a shock-proof plastic box. The GF3 plastic box can be opened with only a single screw for service work. The glide-back protection (only stops the RG7 guiding head, including kink protection) prevents the fibreglass rod from accidentally slipping back into the box. The scope of delivery includes an 16-piece accessory set. The newly developed kink protection technology makes it possible to overcome bending radii of up to R = 38 mm. Total breaking load of 130 kg refers to the glass fibre rod incl. kink protection ending joints.

Optimal field of application: for pipe inner dimension 9 mm - 45 mm.

Application film: You can watch a short, very informative application film by scanning the QR code or at www.runpotec.com.

Scope of supply: 1 x GF3 without metre counter in plastic box, kink protection ending joint on both sides (start / end), contents of the accessory box:

1 x RG7 guiding head with swivel, 1 x kink protection ending joint RTG Ø 6 mm, 1 x pulling grip, 1 x special adhesive 3 g, 1 x cable pull loop (Ø 14 mm outside), 6 x adhesive joint Ø 3 mm, 3 x pulling eye Ø 7 mm, 1 x starting head Ø 11 mm, 1 x connecting joint, 2 x mounting-wrenches

ADVANTAGES

- Guiding head with swivel and kink protection
- Autom. glide back protection (only stops the RG7 guiding head, including kink protection)
- Easy service access
- Shear stable - also for occupied pipes
- Extremely shockproof box with anti-slip coating
- Including cable pulling loop
- Inspektion camera RC2 compatible
- Total breaking load 130 kg

INFORMATION

Compatible with:

RC2 Inspection camera

30 m - Item no.: 10140

50 m - Item no.: 10141

**RC3 Inspection camera (digital)**

15 m - Item no. 10214

