

PIT oe 4S

402311



Pushbutton unit with 4 LED pushbuttons, including fixing nuts. Optional accessories for PIT m4 SEU [402250].

Technical details

General data	
Approval:	CE, UKCA, UL Recognized Component
Technical data	
Electrical data	
Supply voltage (V):	24 - 24 V
Type of supply voltage U1:	DC
Power consumption DC:	0.17 W
Inputs	
Signal level at input at 0:	< 5 V
Environmental data	
Climatic suitability to ...:	EN 60068-2-2, EN 60068-2-1, EN 60068-2-14
Ambient temperature standard:	EN 60068-2-2, EN 60068-2-1
Ambient temperature:	-20 - 60 °C
Storage temperature standard:	EN 60068-2-1/-2
Climatic suitability standard:	EN 60068-2-78
Humidity rating:	93 % r. h. at 40 °C
Perm. operating height ASL:	2000 m
EMC to standard ...:	EN 61131-2 (Zone B)
Vibration to standard ...:	EN 60068-2-6
Acc. shock to standard1:	150 m/s ²

Clearance & creepage dist. to:	EN 61131-2
Overvoltage category:	II
Pollution degree clear.&creep.:	2
Protection type standard:	EN 60529
Protection type, housing:	IP20
Mechanical data	
Mounting position:	any
Connection terminal:	Spring-loaded terminal
Height dimension:	32 mm
Width dimension:	32 mm
Depth dimension:	40 mm
Net weight:	17 g
Gross weight:	25 g
Environment	
WEEE classification (08/2018):	5 devices (feed size < 50cm)
Commercial data	
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27371292
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000017
ETIM Reference Feature:	EC002024
UNSPSC 25:	39122205
GTIN:	4046548097962
Volume:	0 dm3
Harmonized System Code:	85365011
Type of tariff number:	TARIC
Use of customs tariff number:	Ausfuhr, Einfuhr
Quantity per packaging unit:	1