

PSEN me5M NC.NC-NC-NC 1switch

6L000013



Mechanical safety gate system PSENmech, interlock principle magneticforce, contacts interlocking 1 N/C, contacts guard locking 3 N/C, supplyvoltage 24 V AC/DC.

Technical details

General data

Approval:	CSA, CE, CCC, UKCA, DGUV
Suitable for series connection:	yes
unit type:	Sensor

Technical data

Electrical data

Supply voltage (V):	24 - 24 V
Type of supply voltage U1:	AC/DC

Relay outputs

Utilisation cat. AC15/DC13sta.:	EN 60947-5-1
Voltage AC15 safety cont.:	240 V
Max. current AC15 safety cont.:	1.5 A
Voltage DC13 safety cont.:	250 V

Environmental data

Ambient temperature:	-25 - 55 °C
Overvoltage category:	II
Protection type, housing:	IP67

Mechanical data

Holding force:	1500 N
Height dimension:	192 mm

Width dimension:	42 mm
Depth dimension:	44 mm
Net weight:	489 g
Gross weight:	541 g
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	no
REACH compliance:	Contains no SVHC substances
WEEE classification (08/2018):	5 devices (feed size < 50cm)
Commercial data	
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27272603
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000026
ETIM Reference Feature:	EC002593
UNSPSC 25:	39122205
GTIN:	4046548101423
Volume:	1.258 dm ³
Harmonized System Code:	85365080
Type of tariff number:	TARIC
Use of customs tariff number:	Ausfuhr, Einfuhr
Quantity per packaging unit:	1

Optional accessories



570793

PSEN cable 200m-8x0.25mm²



6L000005

PSEN me5 escape release



6L000006

PSEN me5 20mm extension



6L000007

PSEN me5 40mm extension



6L000008

PSEN me5 emergency release front



6L000009

PSEN me5 emergency release back