

PSEN me5M NC.NC-NC M12/8 1switch

6L000020



Mechanical safety gate system PSENmech, with M12 connection 8-pin, interlock principle magnetic force, contacts interlocking 1 N/C, contacts guard locking 2 N/C, supply voltage 24 V AC/DC.

Technical details

General data

Approval:	CSA, CE, CCC, UKCA, DGUV
Suitable for series connection:	yes
unit type:	Sensor

Technical data

Electrical data

Supply voltage (V):	24 - 24 V
Type of supply voltage U1:	AC/DC

Relay outputs

Utilisation cat. AC15/DC13sta.:	EN 60947-5-1
Voltage DC13 safety cont.:	24 V

Environmental data

Ambient temperature:	-25 - 55 °C
Overvoltage category:	II
Protection type, housing:	IP67

Mechanical data

Holding force:	1500 N
Connection type:	M12, 8-pin male
Height dimension:	192 mm
Width dimension:	42 mm

Depth dimension:	44 mm
Net weight:	489 g
Gross weight:	541 g
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	yes
RoHS except.s acc. to direct.:	6c
REACH compliance:	contains min. 1 SVHC-substance
REACH included substances:	Lead
%-part of the pollutant:	> 0,1
CAS No.:	7439-92-1
SCIP entry available:	yes
WEEE classification (08/2018):	5 devices (feed size < 50cm)
Commercial data	
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27272603
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000026
ETIM Reference Feature:	EC002593
UNSPSC 25:	39122205
GTIN:	4046548101492
Volume:	1.258 dm3
Harmonized System Code:	85365080
Type of tariff number:	TARIC
Use of customs tariff number:	Ausfuhr, Einfuhr
Quantity per packaging unit:	1

Optional accessories



540319

PSEN cable axial M12 8-pole 3m



540320

PSEN cable axial M12 8-pole 5m



540321

PSEN cable axial M12 8-pole 10m



540322

PSEN cable angle M12 8-pole 3m



540323

PSEN cable angle M12 8-pole 5m



540324

PSEN cable angle M12 8-pole 10m



540325

PSEN cable angle M12 8-pole 30m



540326

PSEN cable axial M12 8-pole 30m



540332

PSEN/PDP67 M12-8sf screw terminals



540333

PSEN cable M12-8sf, 20m



540334

PSEN/PDP67 M12-8sm screw terminals



540340

PSEN cable M12-8sf M12-8sm, 2m



540341

PSEN cable M12-8sf M12-8sm, 5m



540342

PSEN cable M12-8sf M12-8sm, 10m



540343

PSEN cable M12-8sf M12-8sm, 20m



540344

PSEN cable M12-8sf M12-8sm, 30m



540345

PSEN cable M12-8sf M12-8sm, 0,5m



540346

PSEN cable M12-8sf M12-8sm, 1m

	540347	PSEN cable M12-8sf M12-8sm, 1,5m
	570793	PSEN cable 200m-8x0.25mm²
	630313	PSEN op cable axial M12 8-p. shield. 3m
	630314	PSEN op cable axial M12 8-p. shield. 5m
	630315	PSEN op cable axial M12 8-p. shield. 10m
	630316	PSEN op cable angle M12 8-p. shield. 3m
	630317	PSEN op cable angle M12 8-p. shield. 5m
	630318	PSEN op cable angle M12 8-p. shield. 10m
	630328	PSEN op cable axial M12 8-p. shield. 30m



630329

PSEN op cable angle M12 8-p. shield. 30m



630368

PSEN op cable axial M12 8-p. shield. 50m



630369

PSEN op cable angle M12 8-p. shield. 50m



6L000005

PSEN me5 escape release



6L000006

PSEN me5 20mm extension



6L000007

PSEN me5 40mm extension



6L000008

PSEN me5 emergency release front



6L000009

PSEN me5 emergency release back