

PSEN op2S-1-1

630380



Safety light beam device, Type 2, PL c, body protection, infrared sensor, connection receiver: 4-pin M12 male connector, connection transmitter: 4-pin M12 male connector, connection cable not supplied with the device.

Technical details

General data

Approval:	CE, cULus Listed, TÜV, EAC (Eurasian)
ESPE type:	2
Sensor principle:	Infrared
Resolution protection type:	Body
Operating range (m):	0, 8

Technical data

Electrical data

Supply voltage (V):	20, 30
Type of supply voltage U1:	DC

Optical data

Used wavelength range:	880 nm
------------------------	--------

Environmental data

Ambient temperature:	-25, 55
Climatic suitability standard:	EN 60068-2-3
Humidity rating:	95 % r. h. at 40 °C
Condensation permitted?:	Not permitted
Vibration to standard ...:	EN 60068-2-6
Acc. shock to standard1:	30g
Protection type, housing:	IP67

Times	
Reaction time:	1, 1
Mechanical data	
Connection type:	M12 4-pin
Housing material upper part:	ABS UL 94 V0
Depth dimension:	55
Net weight:	39
Gross weight:	68
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	no
REACH compliance:	Contains no SVHC substances
WEEE classification (08/2018):	5 devices (feed size < 50cm)
Commercial data	
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27272701
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000026
ETIM Reference Feature:	EC001831
UNSPSC 25:	46171620
GTIN:	4046548047752
Volume:	0 dm3
Harmonized System Code:	90314990
Type of tariff number:	TARIC
Use of customs tariff number:	Ausfuhr, Einfuhr
Quantity per packaging unit:	1

Obligatory accessories



630303

PSEN op cable axial M12 4-p. shield. 3m



630304

PSEN op cable axial M12 4-p. shield. 5m



630305

PSEN op cable axial M12 4-p. shield. 10m



630306

PSEN op cable angle M12 4-p. shield. 3m



630307

PSEN op cable angle M12 4-p. shield. 5m



630308

PSEN op cable angle M12 4-p. shield. 10m



630309

PSEN op cable axial M12 4-p. shield. 30m



630319

PSEN op cable angle M12 4-p. shield. 30m